

**USER MANUAL** 

## START UP

Battery Life 3
Timer 4
Cycles Count 5
Detected Atomizer 6
nt Presets Selected 7

(1) (2) () 26

# CONNECTING TO APP

your device to your smartphone via Bluetooth: ode below to find the PCCUS V CARTA app. Download and instruction CARTA. A Meets use Bluetonis is enabled on your phone are blue the device is pointed, start the PCCUS V CARTA APP. The a vicious and prompt you to solot the device you wish to connect will confirm connection. You may now use the app to control or will confirm connection. You may now use the app to control or





## TIME & TEMPERATURE SETTINGS

rom the home screen of your FOCUS V CARTA 2, you can press the DOWN (-) button to adjust the sested emperature setting. Now you, can press the UP (-) or DOWN (-) to adjust the value. The OLED core will display your setting accordingly as you, increase or decrease the temperature. Confirm the orrect selection and let the device return to the home screen to automatically save your settings.

denter the Time Settings mode, press the UP (r) button from the home screen of your FCCUS V ARTA 2. The OI FD screen will display the Time Settings screen, and now you can press the UP (e) or CWM (e) to adjust the duration of your session's time. Let the device return to the home screen to unamatically sow your settings.

# TEMPERATURE RANGE

# 450 ∓ 40s **\$** 100% 450∘⊧



## START YOUR SESSION

er you have set your desired session setting sion. Your FOCUS V CARTA 2 will vibrate a rease. Once at the desired temperature set begin. NOTE: During the countdown sequi-session by 10 seconds. To cancel your ses-



# LED AND SESH PRESETS

Your FOCUS V CARTA 2 comes with five default SESH presers as well as a custom user setting. Press and hold the POWER (0) button to show the SESH presert screen. Press the UP (-) or DOWN (-) buttons to cycle between the preser configurations. Preset 0 will apply user settings.

Out of the box your POCUS VICARTA 2 has five LED presets available to select from Press the POWER (0) button three times to show the LED preset screen, Press the UP(1) or DOWN (-) buttons to cycle between the preset LED configurations. The "DEF" setting will time off all LED and the present of the PoEP setting will time off all LED and the present of the POEP setting will be a set of the POEP set of th

450°F 240s \$ 100% ■

450°F 240s \$ 100% € 1

